

Everled Vertical Optics

50W Vertical optics LED Suspended 4ft
ELV4-DM-40-WH




Performance Summary

Everled Vertical LED linear pendant fixtures integrated with high transmittance PMMA light guide plates. Transparent, vertical optics designed specifically for LED sources are integrated with minimalist design and architectural materials to create a broad range of solutions. No direct or indirect view of the light source with transparent optics when on. It is distributed at a rate of 3:3:4 in horizontal and down directions, precisely controlled optimal distributions for low glare and wide beam angle. Seamless continuous runs speed installation and reduce the labor cost.

Dimension

A: 94.48" / B: 7.87"
C: 0.94"

Dimension



Features

Efficacy: 110LPW

Delivered Light Output: 5500Lumens

Input Power: 50Watts

CRI: Ra>80

DLC CCT Options: 3500K/4000K/5000K

Input Voltage: 100-277V AC

Input current: 0.43A

THD:<20%

Power Factor: >0.9

Standard Warranty: 5 Years

Standard Lifetime: Designed to L70 minimum 50,000 hours


Mounting: Suspended

0-10v dimming

Dimensions: L 47.14" x W 5.51" x H 1.57"

Fixture measurement and weight are round up, pls contact your OKT representative for exact data.

Luminous Intensity Distribution Diagram



AVERAGE BEAM ANGLE[50%]: 149.4°